



**Lubritex Altum
AW Hydraulic Oil
ISO VG 22, 32, 46, 68 & 100**

Product Description

Formulated with high viscosity-index paraffinic base stocks and premium performance additives, Lubritex Altum AW Hydraulic Oils ISO VG 22, 32, 46, 68, 100 exhibit excellent oxidation stability, corrosion protection, shear stability, and pumpability in a wide array of operating conditions and temperatures. The comprehensive additive package includes anti-wear, anti-corrosion, anti-foaming agents as well as detergency. Acceptable for a wide-range of applications, Lubritex Altum AW Hydraulic Oils ISO VG 22, 32, 46, 68, 100 resist oxidation, rust, corrosion, foaming, varnish, and wear.

Typical Properties*

ISO VG	22	32	46	68	100
Appearance, Visual	Yellow, Transparent, Liquid				
Viscosity @ 40°C, cSt, ASTM D445	22.0	32.0	46.0	68.0	100.0
Viscosity @ 100°C, cSt, ASTM D445	4.30	5.47	6.92	8.97	11.40
Viscosity Index, ASTM D2270	100	105	105	105	100
Flash Point, °C, ASTM D92	195	200	205	210	215
Pour Point, °C, ASTM D97	-20	-18	-15	-12	-10

*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

Suitable for Use:

- Parker Denison HF-0, HF-1, HF-2
- MAG IAS P-69 (ISO 68)
- MAG IAS P-68 (ISO 32)
- MAG IAS P-70 (ISO 46)
- GM LS-2
- JCMAS HK
- U.S. Steel 127
- U.S. Steel 136
- Bosch Rexroth RD90220
- SAE MS1004

Product Codes:

- ISO VG 22- SXA605
- ISO VG 32 - SXA606
- ISO VG 46 - SXA607
- ISO VG 68 - SXA608
- ISO VG 100 - SXA609

