



LUBRITEX
HIGH PERFORMANCE LUBRICANTS

PRODUCT DATA SHEET

Lubritex Primus Elite Euro
SAE 5W-40; Full Synthetic Motor Oil
ACEA A3/B4-16, API SN

Product Description

Lubritex Primus Elite Euro SAE 5W-40 Full Synthetic Motor Oil ACEA A3/B4-16, API SN is formulated with synthetic base oils and a premium additive package. This oil is designed for use in carbureted, fuel injected, turbocharged and supercharged gasoline engines. This oil exceeds the performance requirements of API SN and ACEA A3/B4.

Typical Properties*

| <i>SAE J300 Viscosity Grade</i> | <i>5W-40</i> |
|--|----------------------------|
| Appearance, Visual | Amber, Transparent, Liquid |
| Viscosity @ 40°C, cSt, ASTM D445 | 80.0 |
| Viscosity @ 100°C, cSt, ASTM D445 | 13.5 |
| Viscosity Index, ASTM D2270 | 172 |
| CCS Apparent Viscosity, cP, ASTM D5293 | 5,600@-30°C |
| MRV Apparent Viscosity, cP, ASTM D4684 | 23,000@-35°C |
| Flash Point, °C, ASTM D92 | 210 |
| Pour Point, °C, ASTM D97 | -42 |
| Total Base Number, mgKOH/g, ASTM D2896 | 10.5 |

**The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.*

Exceeds Performance Requirements

ACEA A3/B3-16, A3/B4-16
API SN/CF
Porsche A40
MB 226.5 / 229.3 / 229.5
BMW LL-01
VW 502.00, 505.00
Renault RN0700 / RN0710

Product Code

SPE009

